

[Specifications]

Item		ME5804E	ME5808E	ME5816E
Video Input	Input channel	4ch BNC	8ch BNC	16ch BNC
	Input format	All kinds of analog HD (AHD/TVI/CVI)		
Live Display	Interface	1ch VGA, 1ch HD OUTPUT, 1ch SPOT output		
	Resolution	3840x2160, 2560x1440, 1920x1080, 1440x900, 1280x1024, 1280x720, 1024x768		
	Multi display	1ch, 4ch, 6ch, 9ch, 13ch, 16ch		
Multitask		4(Monitoring, Recording, Backup and Monitoring via network)		
Video compression system		H.264, H.265 CODEC selectable		
Recording	Resolution	1920x1080, 1920x540, 960x540, 1280x720, 1280x360, 640x360, 960x480, 960x240, 480x240 (NTSC) 1920x1080, 1920x540, 960x540, 1280x720, 1280x360, 640x360, 960x576, 960x288, 480x288 (PAL)		
	Max. speed	60fps at 1080p (NTSC) 50fps at 1080p (PAL)	120fps at 1080p (NTSC) 100fps at 1080p (PAL)	240fps at 1080p (NTSC) 200fps at 1080p (PAL)
	Frame rate	1, 2, 3, 4, 5, 6, 8, 10, 15, 30 (10 steps) max. 30fps in all resolution		
	Image quality	4 steps (Super, High, Medium, Low)		
	Mode	Continuous, Continuous and Event, Event(sensor, motion detection), Manual, Schedule		
Search	Mode	Quick, Calendar, Bookmark, Event, USB		
Playback	Speed	Playback and reverse playback(x1,x2,x4,x8,x16,x32,x64,x128,x256), slow playback(x1/4,x1/2)		
	Multi display	1ch, 4ch, 6ch, 9ch, 13ch, 16ch		
IO	Sensor input	4 input(NO/NC) terminal		
	Alarm output	1(relay) terminal		
	PTZ control	RS-485 terminal		
	Audio input	4ch		
	Audio output	1ch		
USB		2 ports(USB2.0) for backup and mouse		
Network	Speed	10/100 base-T		
	TCP/IP	Static, DHCP, E-mail, DDNS service		
	Codec	Dual codec (H.264 or H.265)		
	Bandwidth limit	Yes		
Motion dedection		22x15(area), 8 levels(sensitivity)		
Storage	SATA	HDD 2EA		
Backup	Devices	USB flash memory, network		
	File format	AVI, HAV		
	Protection	password protection for playback		
Password protection		Admin/user		
Updating software Method		USB flash memory, network		
Power		AC adaptor input(DC12V 4A)		
Operative temperature, humidity		5°C~40°C, 20%RH~80%RH		
Dimension		320(W) x 330(D) x 70(H)		
Weight		4Kg		