

# [ Specifications ]

Item		ME6804L	ME6808L
Video Input	Input channel	4ch BNC	8ch BNC
	Input format	All kinds of analog HD (AHD/TVI/CVI)	
Live Display	Interface	1ch VGA, 1ch HD OUTPUT, 1ch SPOT output	
	Resolution	3840x2160, 2560x1440, 1920x1080, 1440x900, 1280x1024, 1280x720, 1024x768	
	Multi display	1ch, 4ch, 6ch, 9ch	
Multitask		4(Monitoring, Recording, Backup and Monitoring via network)	
Video compression system		H.264, H.265 CODEC selectable	
Recording	Resolution	2560x1440, 1920x1080, 1920x540, 960x540, 1280x720, 1280x360, 640x360, 960x480, 960x240, 480x240 (NTSC) 2560x1440, 1920x1080, 1920x540, 960x540, 1280x720, 1280x360, 640x360, 960x576, 960x288, 480x288 (PAL)	
	Max. speed	60fps at QHD (NTSC) 50fps at QHD (PAL)	120fps at QHD (NTSC) 100fps at QHD (PAL)
	Frame rate	1, 2, 3, 4, 5, 6, 8, 10, 15, 30 (10 steps) max. 30fps in all resolution	
	Image quality	4 steps (Super, High, Medium, Low)	
	Mode	Continuous, Continuous and Event, Event(sensor, motion detection), Manual, Schedule	
Search	Mode	Quick, Calendar, Bookmark, Event, USB	
Playback	Speed	Playback and reverse playback(x1,x2,x4,x8,x16,x32,x64,x128,x256), slow playback(x1/4,x1/2)	
	Multi display	1ch, 4ch, 6ch, 9ch, 13ch, 16ch	
IO	Sensor input	X	
	Alarm output	X	
	PTZ control	RS-485 terminal	
	Audio input	4ch	
	Audio output	1ch	
USB		2 ports(USB2.0) for backup and mouse	
Network	Speed	10/100 base-T	
	TCP/IP	Static, DHCP, E-mail, DDNS service	
	Codec	Dual codec (H.264 or H.265)	
	Bandwidth limit	Yes	
Motion dedection		22x15(area), 8 levels(sensitivity)	
Storage	SATA	HDD 1EA	
Backup	Devices	USB flash memory, network	
	File format	AVI, HAV	
	Protection	password protection for playback	
Password protection		Admin/user	
Updating software Method		USB flash memory, network	
Power		AC adaptor input(DC12V 3A)	
Operative temperature, humidity		5°C~40°C, 20%RH~80%RH	
Dimension		326(W) x 250(D) x 52(H)	
Weight		2.2Kg	